



**Go green. \$ave some green.**

## HiLine Series XG™ Electric Vehicles

# XG™

### 6-Passenger Low-Speed Vehicle

Today's educated consumer wants the perfect combination of technology, safety and convenience while having peace of mind that they are doing their part to improve the environment.... at a price they can afford.

#### Introducing the HiLine XG™ Series.


Classified as a "low-speed vehicle" (LSV) or "neighborhood electric vehicle" (NEV), the HiLine XG™ has been certified for use in most states on roads with a posted speed limit of 35mph or less, as it has a maximum speed of 25mph.



#### Standard Features

- Maintenance-free batteries
- Easy-to-read digital console with 12V accessory outlet
- Enclosed cargo carrier with security lock
- High-low beam quartz halogen headlamps
- Interior dome light, cup holders, scuff guards, grab handles and floor mats
- Ergonomic, easy-to-clean molded-foam vinyl seating
- Integrated individual padded head restraints
- Adjustable driver, rearview and passenger mirrors
- Front and rear brake lights, turn signals, back-up alarm and hazard lights
- Standard U.S. automotive 3-point strap safety belts
- Tinted automotive safety windshield glass with wiper
- Rack-and-pinion steering for improved control
- Convenient onboard 48-volt DC charging dock for use in any standard 110-volt AC 15-amp outlet and complimentary charging cord set kit
- Dual front independent suspension with coil over double-action shock absorber for a smoother ride
- Each vehicle is thoroughly tested for quality and certified to meet and exceed all FMVSS standards

HiLine XG-6™ Specifications	
Range	Up to 50 miles*
Batteries	48VDC (8 x 6-volt maintenance-free batteries)
Charging Time	Using a standard 110-volt, 15-amp outlet: <ul style="list-style-type: none"> <li>• 80% recharged in 8 to 10 hours</li> <li>• 100% recharged in 12 hours</li> </ul>
Speed	<ul style="list-style-type: none"> <li>• Transition switch allows driver to select 17mph (golf course path) or 25mph (road)</li> <li>• Top speed is 25mph, according to FMVSS 500 for LSV/NEV/ZEV</li> </ul>
Curb Weight	1,896 lbs
GVWR	2,970 lbs
Payload Capacity**	1,440 lbs
Configuration	6-Passenger
Dimensions (HxWxL)	70"H x 60"W x 164"L
Wheelbase	133"
Turning Circle	39 ft.
Tires	Street-rated, 13-inch steel radial tubeless tires
Body	<ul style="list-style-type: none"> <li>• All-steel frame with rust protection primer and plastic powder coating</li> <li>• Fiberglass body panels</li> </ul>
Propulsion	<ul style="list-style-type: none"> <li>• Front wheel drive</li> <li>• Heavy-duty 6HP DC motor</li> <li>• Curtis 1268 controller with voltage self-check</li> </ul>
Braking System	<ul style="list-style-type: none"> <li>• Double-circuit, full hydraulic, front-wheel disc, rear-wheel drum, regenerative braking system for optimum driving range and safety</li> <li>• Parking brake for inclines</li> </ul>
*Range will vary depending on terrain, driving style and/or vehicle payload.	
**Options + passengers + cargo	



HiLine Carts & Cars Inc.

P.O. Box 72660, Newnan, GA 30271 USA

Phone: 770.783.2797 Fax: 866.927.9966

www.xgreencars.com e: sales@xgreencars.com

HiLine Carts & Cars Inc. reserves the right to change specifications, components and suppliers at any time without giving notice.